

Jane Addams Memorial Tollway (I-90)
Outside Roadway and Bridge Reconstruction and Widening
Roselle Road to I-290 /IL 53
Milepost 65.5 to Milepost 68.1

Cook County, Illinois.

Target Advertisement Date: October 2014

The work under this contract includes but is not limited to: pavement removal and shoulder removal, mainline reconstruction and widening, reconstruction of the westbound exit ramp and eastbound entrance ramp at the interchange with Roselle Road, construction of a westbound exit ramp and westbound entrance ramp at Meacham Road, construction of eastbound exit ramp to Roselle Road, retaining wall and noise abatement wall construction, maintenance of traffic during construction, temporary and permanent erosion control devices, guardrail installation and removal, pavement marking and signing, mainline and underpass lighting.

DESCRIPTION	UNIT	QUANTITY
PORTLAND CEMENT CONCRETE PAVEMENT 13" (JOINTED)	SQ YD	142,000
PERFORMANCE BASED SOIL REMEDIATION	SQ FT	103,000
FURNISHED EXCAVATION	CU YD	85,000
STABILIZED SUBBASE – WMA, 3"	SQ YD	180,000
EARTH EXCAVATION	CU YD	100,000
WARM-MIX ASPHALT SHOULDERS (9 IN.)	SQ YD	67,000
PERFORMANCE BASED RETAINING WALL	SQ FT	35,000
CATCH BASINS, TYPE G-4 (SPECIAL), TYPE G-3 FRAME AND GRATE	EACH	60
PAVEMENT REMOVAL	SQ YD	100,000
TRENCH BACKFILL	CU YD	40,000
FURNISH AND INSTALL TEMPORARY CONCRETE BARRIER, TO REMAIN IN PLACE	FOOT	31,000
PORTLAND CEMENT CONCRETE PAVEMENT 10" (JOINTED)	SQ YD	18,000
UNDERGROUND CONDUIT, COILABLE NONMETALLIC CONDUIT, 3" DIA.	FOOT	57,000

SUBGRADE AGGREGATE, SPECIAL, 9"	CU YD	65,000
WARM-MIX ASPHALT SHOULDERS, 6"	SQ YD	32,000
CONCRETE BARRIER, DOUBLE FACE, VARIABLE HEIGHT	FOOT	9,000
STORM SEWERS, CLASS A, TYPE 2, 66"	FOOT	5,000
CONCRETE BARRIER , SINGLE FACE, REINFORCED, 42 INCH	FOOT	10,000
CATCH BASINS, TYPE G-4 (SPECIAL), TYPE 20A FRAME AND GRATE	EACH	40
PIPE UNDERDRAINS, FABRIC LINED TRENCH, 6"	FOOT	64,000
TOPSOIL REMOVAL AND DISPOSAL	CU YD	41,000
STORM SEWERS, CLASS A, TYPE 2, 72"	FOOT	3,000
CATCH BASINS, TYPE G-4 (SPECIAL), TYPE G-2 FRAME AND GRATE	EACH	30
CONCRETE SUPERSTRUCTURE	CU YD	650
TEMPORARY CONCRETE BARRIER	FOOT	18,000
CATCH BASINS, TYPE G-3 (MODIFIED), TYPE G-3 FRAME AND GRATE	EACH	70
CONCRETE BARRIER BASE, 5'	FOOT	9,000
STORM SEWERS, CLASS A, TYPE 2, 54"	FOOT	4,000
PAVED SHOULDER REMOVAL	SQ YD	50,000
WET REFLECTIVE TEMPORARY TAPE TYPE III, 4"	FOOT	500,000
RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	110,000

The above project description reflects major pay items for this contract and does not include all items. All quantities included above are estimates. Refer to bid documents for actual quantities.